



Cyclades 50.4



Cyclades 50.5

## GENERAL SPECIFICATIONS

• L.O.A	15.65 m
• Length of hull	15.24 m
• L.W.L.	13.18 m
• Width of hull	4.90 m
• Lightweight	12 680 kg
• Draft (min) - Cast iron	2.00 m
• Ballast weight	3 950 kg
• Air draught	20.90 m
• Fuel tank capacity	400 l
• Freshwater capacity	980 l
• Engine power	110 HP

## ARCHITECTS / DESIGNERS

- Berret-Racoupeau

## EC CERTIFICATE

- Category A - 13 persons
- Category B - 14 persons
- Category C - 16 persons

## STANDARD SAIL LAYOUT AND AREA

• Mainsail	60.50 m <sup>2</sup>
• Genoa	110 % - 49.50 m <sup>2</sup>
• Asymmetric spi	140.00 m <sup>2</sup>
• I	18.25 m
• J	5.45 m
• P	16.74 m
• E	5.90 m

## STANDARD EQUIPMENT

### CONSTRUCTION

Design made following European Directive requirements and according to EC certification

- Monolithic design hull, layered with balsa-wood sandwich
- Structural counter moulding - laminated and stuck to specific parts of the hull
- Deck in sandwich glass fibre and balsa wood, Diamond tip type non-slip surface
- Deck inner moulding complete
- Deck hull join with aluminium footrests with wood inserts - Stern deck hull join with rubber bevel
- Fixed keel in cast iron, fixed with a system of screws and stainless steel veneer
- Rudder hung with glass compound stock
- White coloured hull - Anthracite grey hull decoration

### DECK EQUIPMENT

#### RIGGING

- Standard mast 9/10 electro-polished aluminium installed on the deck, 2 level(s) of advanced cross trees
- Boom in electro-polished aluminium
- Standing rigging in stainless steel discontinuous
- 2 Backstays with turnbuckles
- Rigid boom down-haul with tackle 4 strands
- 1 Genoa furling system with drum on the deck
- 1 Mainsail sheet tackle with chain plate on deck house
- 2 genoa sheet tracks with piston adjusted traveller cars - 2 Genoa sheet return blocks
- Complete running rigging: 1 Main halyard - 1 Genoa halyard with clutch on mast and cleat - 1 Boom topping lift with cleat on mast - 1 Mainsail foot - 2 Genoa sheets - 2 fast reefing ropes
- 2 clutches to port - 6 clutches to starboard
- Bollards

#### WINCHES

- 2 Self-tailing genoa sheet winches (H 53.2 STA)
- 1 Rigging winch to starboard (H 44.2 STA)
- 2 Winch handles aluminium
- 2 Winch handle box(es)

#### SAILS

- Furling genoa with UV protective strip
- Semi full batten written mainsail with slider
- Lazy-jacks - Lazy-bag blue and sand colour

#### MOORING -ANCHORING

- Self-bailing chain locker - Clench bolt - Hatch cover
- 2 Bow rollers in stainless steel
- Electric windlass horizontal 1700 W - Remote control
- 6 Aluminium mooring cleats - 8 Fairleads

#### SAIL LOCKER

- Height to deck beam: 1.81 m
- Access through deck hatch
- Stainless steel ladder
- Side cubbyholes

## PERSONNEL GUARDS

- 1 Half-open stainless steel forward pulpit
- 2 stainless steel aft pushpits
- 1 Ring lifebuoy bracket
- 1 Outboard engine bracket
- 1 Flag pole socket
- Double guardrails - Stainless steel stanchions
- Gangway opening to port and to starboard
- 2 Natural solid wood handrails on the deck house

## COCKPIT

- Cockpit bottom self bailing
- 4 Storage lockers
- 1 Life raft locker in cockpit bottom
- Cockpit bench seats in polyester - non-slip finish
- 2 Steering wheel consoles: Stainless steel steering wheels - Diameter 900 - rudder systems on partition - Metal cable transmission system with feedback to tiller sector
- 1 Deck hole for access to tiller system - 1 Emergency tiller in stainless steel
- 2 Steering compass on binacelle
- Engine control - Control panel to starboard
- Polyester cockpit table - 2 flaps - Glove box - Glass holder - bottle holder - hand rail - Reclined panel for electronic navigation screen (optional instruments)
- 2 Companionway door on solid wood hinges - Sliding hatch made of PMMA
- 2 Waterproof loudspeakers

## SUN DECK AND UPPER STERN

- 1 Retractable access door in cockpit bottom
- Swim deck in polyester - non-slip finish
- 1 Stainless steel swimming ladder
- 1 Cockpit shower spray cold water to starboard
- 1 Gas box 2 bottles to port - 1 watertight locker to starboard

## LAYOUTS

- Cherry coloured Alpi woodwork
- Parquet type laminated floors
- Spar ceiling

## COMPANIONWAY

- Height to deck beam: 2.05 m
- Companionway and steps in polyester - Non-slip
- 2 Wooden handrail(s)

## 2 FORWARD CABINS

- 2 Symmetrical cabins each one consisting of:
  - Height to deck beam: 1.94 m
  - Triangle double bed (2.02 m x 1.48 m x 0.90 m) - Marine mattress
  - Hanging locker - Cubby hole lockers - Storage
  - 1 Opening deck hatch with mosquito blind
  - 1 Opening portholes in coaming

## 2 WASH ROOMS FORWARD

- 2 Symmetrical washrooms, private access from cabins, each with:
  - Height to deck beam: 1.95 m
  - Marine toilet
  - Polyester washbasin - Mixer tap / Shower spray hot water / cold water
  - 1 Mirror
  - Toilet accessories
  - 1 Opening portholes in coaming

## SALOON TO STARBOARD

- Height to deck beam: 2.02 m
- U shaped saloon bench
- Wooden saloon table (2.20 m x 0.50 m) - Aluminium legs
- Central cupboard with: Beading hand rail - 1 Ice box 130 litre with Refrigeration unit 12 V - 1 Bench seat with storage - Drawers - Cupboards - Rubbish bin
- Cubbyholes along the hull
- 1 Opening deck hatch with mosquito blind
- 2 Opening portholes in coaming

## CHART TABLE TO STARBOARD

- Height to deck beam: 1.95 m
- Control console with flap - glove boxes - Shelf case - Moulded wood beading
- Helmsman seat with locker
- Navigation instrument panel (without instruments)
- Electrical panel
- 1 Fixed porthole in coaming

## GALLEY TO PORT

- Height to deck beam: 2.00 m
- Laminated worktop
- Stainless steel sink 2 basin
- 1 Mixer tap cold water / hot water
- Stainless steel 2 hob gas oven cooker on mounting - safety bar
- 1 Ice box 170 litre - Refrigeration unit 12 V - top opening
- Rubbish bin
- Closed lockers - Cutlery drawer - Storage space
- Bar cupboard, shelves with door (Cyclades 50.4)
- 3 Opening portholes in coaming (Cyclades 50.4)
- 2 Opening portholes in coaming (Cyclades 50.5)
- 1 Opening deck hatch with mosquito blind

## AFT TOILET TO PORT (CYCLADES 50.4)

- Height to deck beam: 2.00 m
- Marine toilet
- Polyester washbasin, Mixer tap / Shower spray hot water / cold water
- 1 Mirror
- Toilet accessories
- 1 Rigid sewage water tank 80L
- 1 Opening portholes in coaming

## PORT CABIN (CYCLADES 50.5)

- Height to deck beam: 2.00 m
- 2 Bunk berths (2.02 m x 1.35 m / 0.40 m) - Marine mattress
- Foldaway upper berth
- Hanging locker - Storage
- 2 Opening portholes in coaming

## AFT TOILET TO STARBOARD

- Height to deck beam: 2.00 m
- Marine toilet
- Polyester washbasin, Mixer tap / Shower spray hot water / cold water
- 1 Mirror
- Toilet accessories
- 1 Rigid sewage water tank 80L (Cyclades 50.5)
- 1 Opening portholes in coaming

## 2 AFT CABIN

- 2 Symmetrical cabins each one consisting of:
  - Height to deck beam: 2.00 m
  - Double bed (2.02 m x 1.52 m / 1.03 m) - Marine mattress
  - Hanging locker - Cubby hole lockers
  - 1 Opening cockpit porthole
  - 1 Deck house opening portholes
  - 1 Opening hatch with mosquito blind

## ENGINE

- Engine Yanmar Diesel 110 hp
- Engine control - Key ignition - Control panel in cockpit
- Engine compartment: Soundproofing foam - Ventilation: 1 air intake and 1 pressured air outlet
- 1 ALTERNATOR 12V 80 Amperes
- 2 Rotation moulded diesel tank (2x200 L - under aft berths) - Electrical gauge - 1 Deck filler
- Filters: Sea water - Diesel - Decanter
- Stainless steel shaft line - Polyester guard moulded into hull
- Fixed three blade propeller
- 1 Engine access through companionway (opening secured with prop) - 2 Engine access through aft cabins

## ELECTRICITY

- 12 V circuit - 220 V circuit
- 2 service batteries (2x140 Amperes) - 1 Battery for engine (1x110 Amperes)
- 2 Battery chargers (25 Amperes) - 1 Shore power 220V - 1 Relay coupler
- Electrical panel (12 V / 220V): Circuit breakers - Decomposed switch - Fuses - Voltmeter - Battery warning - Water gauge - Fuel gauge
- 2 Sockets 220V
- Lighting: Halogen ceiling lights - Reading lights
- Navigation lights: Forward and aft navigation lights - Navigation light and mooring light on mast
- Wire runs for options cables

## PLUMBING

- 3 rotation moulded freshwater tanks 980 l (under forward cabin berth and in the saloon) - 3 Deck fillers - Tank selection with ¼ by-pass valves - Electrical gauges
- Pressurised electric water pump - Expansion chamber - System protection filter
- Electric water heater 40 L
- 1 Freshwater foot pump
- Electrical shower drain pumps
- 1 Electric bilge pump - 1 Manual bilge pump

## GAS

- 2 Gas bottle boxes
- Pressure reducing valve and safety tap

## TRIM LEVEL

	CLUB
Foldaway deck house hood or fixed bimini roof or standard Bleu Captain bimini roof	■
Cockpit benches decked in natural solid wood	■
1 Port rigging winch H44.2 STA with clutch	■
Leather covering on 2 steering wheels	■
Table leg column for double berth in saloon	■
10 person crockery set	■
Mooring kit (Anchor SOC 24 kg - 40 m of chain - 40 m of rope) - 4 Mooring ropes - 6 Fenders	■
Tridata Loch speedo sounder ST 60+ RAYMARINE	■
Anemometer wind indicator ST60+ RAYMARINE	■
1 Multifunction colour screen C80 LCD 8.4 inch (GPS, tracker, Cartography chart mapper Navionics Gold - supplied without chart) RAYMARINE	■
Pilot ST 6002, Piston LS RV2, Control console RAYMARINE	■

## OPTIONS

### OTHER OPTIONS

- VHF RAYMARINE 49E
- 2 flag halyards
- Electropolished mast furling system with main sail
- Electrical rigging winch To starboard 44.2 STAEH
- Bleu captain cockpit cushions
- Bow thruster
- Generator 7 KVA
- Fridge 80 l front opening (For Cyclades 50.4)
- Microwave oven
- Additional rigid sewage tank
- 2 Additional service batteries (2x140 Amperes)

### Bow cabin (In place of the sail hold)

- Access through deck hatch
- Stainless steel ladder
- Fold-down couchette (1.95 m x 0.40 m)
- Bedside cabinet with washbasin mixer tap (hot/cold)
- Marine toilet